

INVENTORS

NADRIATUL SYAFIKA BT MOHD PITERAH NUR ATIKAH BT ZULKANAINI MOHD FIKRI B. CHE HUSIN AHMAD FARIZ B.HASAN

CONTACT DETAILS

Department of Electronic Engineering,
Faculty of Engineering Technology,
Universiti Malaysia Perlis (UniMAP), Kampus
Uniciti Alam, Sg. Chuchuh, 02100 Padang
Besar, Malaysia.
E-MAIL: FIKRI@UNIMAP.EDU.MY
H/P NO.:013-5235005

GREENHOUSE MONITORING SYSTEM




PRODUCT DESCRIPTION

A greenhouse is a building where plants are grown. Light and temperature control allows greenhouses to turn in-arable land into arable land, thereby improving food production in well environments." By the combining effective irrigation and ventilation, it will monitor the a suitable environment. It is preferable to have automated system to control when you are out during the day. The controller used is 8-bit microcontroller called 8051. Moisture meter are communicated with chip to control the operation of irrigator according to the moisture condition in soil. This sensors use capacitance to measure the dielectric permittivity of a surrounding medium.

NOVELTIES

- Control soil moisture and temperature automatically
- · Low cost
- Low energy consumption

PRODUCT PERFORMANCES









PROCESS FLOW





TABLE OF OPERATION OF MOISTURE CONTROL

MOISTURE	STATUS OF MOTOR	TIME FOR ON (second)	TIME FOR OFF (second)
0	ON	5	
1	ON		
2	ON	3	
3	ON	2	
4	OFF		4

POTENTIAL APPLICATION

This project has been met all of objective in control greenhouse environment which are to achieve maximum Plant growth and yield, to control soil and moisture Temperature and to reduce cost of maintaining a Conventional greenhouse powered by low power.

- •It is also quite flexible because the moisture of soil can be set using Potentionmeter to adjust the Vin (-) of ohmamp.
- •It is also quite flexible because the moisture of soil can be set using Potentionmeter to adjust the Vin (-) of ohmamp.



Moisture	Output voltage(mV)	
1		OPTIMO
2	-	
3		
4		
5	117.7	
6		
7		
8		
9		
10	300.0	